

# DIMMERFLIGHT

## EASYFLIGHT

The digital EASYFLIGHT is based on the tested EASY 12 dimmerpack technology. It is designed for all types of tours, requiring mobility and strength. The friendliness of the user's interface makes a safe operation in all circumstances. Its advantageous price is appropriate for all budgets

- ♦ **Detection, visualization**, protection against wrongful connections
- ♦ **Animation** and **test** programs
- ♦ **32000 steps**: very high precision
- ♦ Protection by single pole + neutral fuse
- ♦ Temperature checking by microprocessor
- ♦ DMX 512 digital control
- ♦ Assignment by 3 coding selectors
- ♦ Local tests
- ♦ Commutable DMX connection
- ♦ Connections on: double NF, schuko, CEE or multipin Hartings connectors
- ♦ Reinforced flights with retractable handles and 2 removable covers.



### Configurations

12 x 2,3 kW  
24 x 2,3 kW

### Dimensions & Weight

	Width (mm)	Height (U)	Depth (mm)	Weight (kg)
<b>2976</b>				
12 x 2,3 kW	520	4U	630	28
<b>2975</b>				
24 x 2,3 kW	520	12U	630	60

EASYFLIGHT



## GENERAL SPECIFICATIONS

- Assignment number selection of the first DMX circuit (1 to 512)
- Local tests by steps of 10%
- Chaser selection among nine with its running speed
- Curve: linear
- Last DMX level held in the event of DMX signal loss
- LED power indicator and fault signalization
- LED: OK, DMX signal and temperature
- Models

<b>2976</b>	12 x 2.3 kW	connection on double 2+ T 10/16A NF sockets
<b>2976CE</b>	12 x 2.3 kW	connection on CEE 2+T 16A sockets
<b>2976HA</b>	12 x 2.3 kW	connection on multipin HARTING 16 connectors
<b>2975</b>	24 x 2.3 kW	connection on double 2+ T 10/16A NF sockets
<b>2975CE</b>	24 x 2.3 kW	connection on double CEE 2+T 16A sockets
<b>2975HA</b>	24 x 2.3 kW	connection on multipin HARTING 16 connectors

## TECHNICAL SPECIFICATIONS

Power supply	: TRI +N+T 230/400V, 50/60Hz on CEE connector 5x63A or 5x125A
Protection	: UNI+N 10A HPC fuse on each output
SCR control	: Digital for all types of control
Circuit outputs	: Sockets
Control	: DMX 512 on XLR5
Environment	: Temperature 0° to + 40°C, Humidity 0 to 90%
Cooling	: Noiseless fans
Operation	: Leading edge dimming
Source compatibility	: Incandescence, Halogen 230, Ferro magnetic transformer halogen, Fluo (contact us)
CEM compatibility	: According to EN 55014 60669 / 60439 standards

## OPTIONS

Option 07	: Circuit protection with UNI + N 10A MCB
Option 42	: 4x40A 30mA RCCD by group of 12 circuits
-----	: 4 casters (2 with brakes) base
Shuko / Swiss	: Shuko or Swiss sockets
Customization (Fab dos)	: EASYFLIGHT specific configuration

## DESCRIPTION



CE marked according to the EEC/89/336 and EEC/73/23 - Environment 1.  
This device is designed for working on private or public NF EN 50160 network.

Photo: actes.sceno

an\_easyflight\_ft0 15/11/06 RVE Technologie reserves the right to make any variation in design or construction to the equipment described without prior notification.



RVE

Phone: +33 (0)1 48 54 31 63, Fax: +33 (0)1 45 28 67 53, E-mail: [commerce@rvetec.com](mailto:commerce@rvetec.com), Website: [www.rvetec.com](http://www.rvetec.com)